



AXBUCS-SB286V2

INSTALLATION INSTRUCTIONS

Steering Wheel Control Harness

Fits Select Subaru Models **2013-2014**

* Visit AxxessInterfaces.com for more detailed information about the product and up-to-date vehicle specific applications

INTERFACE FEATURES

- Pre-wired for the Axxess SWC interface (sold separately)
- Retains the factory backup camera and the factory AUX-In jack
- Provides NAV outputs (reverse)
- Includes the AXCS-D-6V 12-volt to 6-volt converter

Note: The aftermarket radio must have an AUX-IN port

INTERFACE COMPONENTS

- AXBUCS-SB286V2 harness • AXCS-D-6V

TOOLS REQUIRED

- Crimping tool and connectors, or solder gun, solder, and heat shrink
- Tape • Wire cutter • Zip ties

CAUTION! All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before cycling the ignition. Also, do not remove the factory radio with the key in the on position, or while the vehicle is running.

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/19/25



AXBUCS-SB286V2

INSTALLATION INSTRUCTIONS

Connections

- Connect the **Black** wire to chassis ground, and also to the **Black** wire from the AXCSD-6V.
- Connect the **Red** wire labeled "Camera Power 6V" to the **Blue/Red** wire from the AXCSD-6V.
- If retaining steering wheel controls: connect the **Red** wire labeled "AXSWC 12V Accessory" to accessory power.
- Connect the **Green/Purple** wire to the reverse wire from the radio, and also to the **Blue/White** wire from the AXCSD-6V.
- Connect the **Yellow** RCA jack to the backup camera input from the radio.
- If retaining the factory AUX-IN jack, connect the **Red** and **White** RCA jacks to the AUX input from the radio.

The following (2) wires are for aftermarket multimedia/navigation radios that require these wires:

- Connect the **Blue/Pink** wire to the VSS/speed sense wire.
- Connect the **Light Green** wire to the parking brake wire.

Installation

1. After the radio has been tested and verified working properly, remove the key from the ignition. Connect the AXBUCS-SB286V2 harness to the wiring harness in the vehicle, then to the Axxess SWC interface.
2. Refer to the Axxess SWC interface instructions for radio connections and programming. Disregard the harness that comes with the Axxess SWC interface.



Metra recommends MECP
certified technicians

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION

REV. 6/19/25



AXBUCS-SB286V2

INSTALLATION INSTRUCTIONS

Arnés de control del volante

Compatible con modelos Subaru selectos **2013-2014**

* Visite AxxessInterfaces.com para obtener información más detallada sobre el producto y aplicaciones actualizadas específicas para vehículos.

CARACTERÍSTICAS DE LA INTERFASE

- Pre-cableado para la interfaz Axxess SWC (se vende por separado)
- Conserva la cámara de reversa de fábrica y la entrada AUX-In original
- Proporciona salidas de navegación (reversa)
- Incluye el convertidor AXCS-D-6V de 12 voltios a 6 voltios

Nota: El estéreo del mercado secundario debe tener una entrada AUX-IN

COMPONENTES DE LA INTERFASE

- Arnés AXBUCS-SB286V2 • AXCS-D-6V de 12 voltios al convertidor de 6 voltios

HERRAMIENTAS REQUERIDAS

Pinzas de engarzar y conectores, o pistola de soldar, soldadura y tubo termocontráctil

- Cinta (adhesiva) • Cortador de cables • Cinchos (de plástico)

CAUTION! All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before cycling the ignition. Also, do not remove the factory radio with the key in the on position, or while the vehicle is running.

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION

REV. 6/19/25



AXBUCS-SB286V2

INSTALLATION INSTRUCTIONS

Conexiones

- Conecta el cable **negro** a tierra del chasis, y también al cable **negro** del AXCS-D-6V.
- Conecta el cable **rojo** etiquetado como "Camera Power 6V" al cable **azul/rojo** del AXCS-D-6V.
- Si se van a conservar los controles del volante: conecta el cable **rojo** etiquetado como "AXSWC 12V Accessory" a la corriente de accesorio.
- Conecta el cable **verde/morado** al cable de reversa del estéreo, y también al cable **azul/blanco** del AXCS-D-6V.
- Conecta el conector RCA **amarillo** a la entrada de cámara de reversa del estéreo.
- Si se va a conservar la entrada AUX-IN de fábrica, conecta los conectores RCA **rojo y blanco** a la entrada AUX del estéreo.

Los siguientes (2) cables son para estéreos/multimedia o navegadores aftermarket que los requieran:

- Conecta el cable **azul/rosa** al cable de señal de velocidad (VSS).
- Conecta el cable **verde claro** al cable del freno de mano.

Instalación

1. Después de probar el estéreo y verificar que funciona correctamente, retira la llave del encendido. Conecta el arnés AXBUCS-SB286V2 al arnés del vehículo y luego a la interfaz Axxess SWC.
2. Consulta las instrucciones de la interfaz Axxess SWC para las conexiones y programación del estéreo. Ignora el arnés que viene con la interfaz Axxess SWC.



Metra recommends MECP
certified technicians

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION

REV. 6/19/25