


<b>A1. Model No.:</b>		<b>A2. Product Name:</b>	
SV-HDW135897CAI		Digital 1080P Wireless Camera with Built-in Battery and Magnet	
<b>B1. Product Keywords:</b>			
1) 1080P High Resolution 2) Waterproof: IP69K approved 3) Working status switch button, switch between work/sleep mode; 4) Battery capacity indicator; 5) Overcharging/Overdischarging protection 6) Short-circuit protection; 7) Overheat and low temperature protection; 8) Strong magnetic base 9) When monitor enters standby mode for 20s, or switch to other channel, camera will enter standby mode; when monitor goes back to work, camera will be woken up and work;(When monitor and camera both have Low power module) 10) Low power consumption :less than 1.5mW at sleep mode; less than 10mW at standby mode. 11) Strong magnetic base			
<b>B3. Key Specifications:</b>			
Battery Capacity	3.6V/6700mAh	<div style="border: 2px solid red; padding: 10px;"> <p style="text-align: center;"><b>TIPS</b></p> <p>1. To protect the battery from damage, please charge it to 75% of capacity before storing it for a long period of time, and charge it again to 75% within 150 days.</p> <p>2. After stored for long time, the initial charging current might be relatively low, but will become normal after a while.</p> <p>3. AC Adapter(Charger) is recommended for charging use.</p> </div>	
Charging Voltage	DC 5~12V		
Charging Time	5V/8H, 12V/3H		
Charging Current	5V/1.5A(MAX), 12V/1.5A(MAX)		
Discharging Time	9H (Daytime) 5H(nighttime)		
Charging Temperature	-10 ~ 45℃		
Discharging Temperature	-20 ~ 60℃		
Storage Temperature	-20 ~ 60℃		
Waterproof Rating	IP69K		
Dimension	116*80*66 (mm)		
Weight	670 g		
Image Device	1/2.9" CMOS		
Effective Pixels	1920 (H) x 1080 (V)		
Pixel size	4.2um*4.2um		
Scanning System	Progressive Scanning		
Sync. System	Internal		
AGC	Auto		
S/N Ratio	38dB		
White Balance	Auto		
BLC	Auto		
Operation Frequency:	2403MHz-2478MHz		
Receiving Sensitivity:	-78dBm		
Video Codec:	H.264		
Frame Rate:	25/30fps		
Transmission Power	FCC: ≤26dBm CE: ≤20dBm MIC: ≤10dBm		
Transmission Distance	FCC: ≤300m CE: ≤200m MIC: ≤60m		
Spread SPECTRUM:	DSSS		
Delay:	170ms		
RF Bit Rate:	12Mbps		
Minimum Illumination	0.1 Lux (day), 0 Lux (with IR)		
Power Supply	DC 10~32V		
Night vision distance	8~10m		
Waterproof rating	IP69K		
Viewing Angle	130°		
Weight Of Unit Product:	0.75 KG 0.85 KG (with adapter)	Weight Of Export Carton:	3.5 KG 4 KG (with adapter)
Dimension Of Giftbox:	12.8*15.4*7.7 CM	Dimension Of Export Carton:	27.6*17.2*18.4 CM
20"/40"/40"HQ Qty:		Qty Per Carton:	4 PCS
<b>E1. Payment Term:</b>		<b>F1. Warranty Terms:</b>	
		18 months of warranty	
<b>G1. Certificates:</b>		<b>H1. Reference Price:</b>	
		Sample:	Lead time:
		Adapter Optional:	