

strands®

-lighting division




Part No. 830429
REAR POSITION LIGHT LED



Part No. 830430
FRONT POSITION LIGHT LED



Part No. 830431
SIDE MARKER LED



FREEDOM VIKING DARK



PART NO.	830429	830430	830431
VOLTAGE	12-24V DC	12-24V DC	12-24V DC
CONSUMPTION	1,7W	3,6W	3,6W
FUNCTIONS	Rear position light	Front position light	Side marker
IP-CLASS	IP6K9K	IP6K9K	IP6K9K
COLOR LENS	Outer lens-Clear/Inner lens- Dark	Outer lens-Clear/Inner lens- Dark	Outer lens-Clear/Inner lens- Dark
COLOR LED	Red	White	Amber
CONNECTION	Cable	Cable	Cable
CABLE LENGTH	1000 mm	1000 mm	1000 mm
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate
HEIGHT	32 mm	32 mm	32 mm
DIAMETER	70,2 mm	70,2 mm	70,2 mm
OPERATING TEMPERATURE	-40°C - +40°C	-40°C - +40°C	-40°C - +40°C
ADR-APPROVED	No	No	No
E-APPROVED	R148	R148	R148
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10

THE PERFECT SOLUTION FOR YOU WHO WANT THE FREEDOM TO CHOOSE YOURSELF.

Option 1.

The minimum quantity for own logo is 1000 pcs.

It is possible to combine articles 830401-830404 freely.

E.g. 500 pcs 830401, 200 pcs 830402, 100 pcs 830403 and 200 pcs 830404.

Option 2.

Minimum quantity 200 pcs. It is possible to combine

articles 830401-830404 freely. For example. 100 pcs

830401, 50 pcs 830402, 50 pcs 830403.

Additional start-up cost for logo: SEK 15,000.

Contact us to find out more about how to maximize your own personality.




Part No. 830429
REAR POSITION LIGHT LED



Part No. 830430
FRONT POSITION LIGHT LED



Part No. 830431
SIDE MARKER LED



FREEDOM VIKING DARK



PART NO.	830429	830430	830431
VOLTAGE	12-24V DC	12-24V DC	12-24V DC
CONSUMPTION	1,7W	3,6W	3,6W
FUNCTIONS	Rear position light	Front position light	Side marker
IP-CLASS	IP6K9K	IP6K9K	IP6K9K
COLOR LENS	Outer lens-Clear/Inner lens- Dark	Outer lens-Clear/Inner lens- Dark	Outer lens-Clear/Inner lens- Dark
COLOR LED	Red	White	Amber
CONNECTION	Cable	Cable	Cable
CABLE LENGTH	1000 mm	1000 mm	1000 mm
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate
HEIGHT	32 mm	32 mm	32 mm
DIAMETER	70,2 mm	70,2 mm	70,2 mm
OPERATING TEMPERATURE	-40°C - +40°C	-40°C - +40°C	-40°C - +40°C
ADR-APPROVED	No	No	No
E-APPROVED	R148	R148	R148
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10